



Electrodes, long

Electric strength up to 6000 Vp, hexagon coding

Heat-resistant safety insulation guarantees electric strength up to 6000 Vp. Twist-proof work thanks to hexagon coding.

Intended use: Monopolar electrodes are used for electrosurgical cutting and coagulation with monopolar handles.

Packaging unit: 1 pc.

Electric strength: 6000 Vp

Preparation: 75 cycles

Article no.	Article designation	Permissible combinations	Ø Shaft	Electrode type	Electrode shape
520-028	Knife electrode, straight, 154 mm, insulated shaft 4 mm	Reusable 4 mm handles	4 mm	Knife electrode	Straight
530-028	Knife electrode, straight, 152 mm, insulated shaft 2.4 mm	Reusable 2.4 mm handles	2.4 mm	Knife electrode	Straight
520-124	Knife electrode, straight, rhombic, 142 mm, insulated shaft 4 mm	Reusable 4 mm handles	4 mm	Knife electrode	Straight, rhombic
530-224	Knife electrode, rhombic, 146 mm, insulated shaft 2.4 mm	Reusable 2.4 mm handles	2.4 mm	Knife electrode	Straight, rhombic
520-123	Knife electrode, angled, rhombic, 142 mm, insulated shaft 4 mm	Reusable 4 mm handles	4 mm	Knife electrode	Angled, rhombic
530-123	Knife electrode, angled, rhombic, 146 mm, insulated shaft 2.4 mm	Reusable 2.4 mm handles	2.4 mm	Knife electrode	Angled, rhombic
530-225	Needle electrode ENT, angled, 124 mm, insulated shaft 2.4 mm	Reusable 2.4 mm handles	2.4 mm	ENT electrode	Angled
520-027	Needle electrode, straight, 136 mm, insulated shaft 4 mm	Reusable 4 mm handles	4 mm	Needle electrode	Straight

Article no.	Article designation	Permissible combinations	Ø Shaft	Electrode type	Electrode shape
530-027	Needle electrode, straight, 140 mm, insulated shaft 2.4 mm	Reusable 2.4 mm handles	2.4 mm	Needle electrode	Straight
520-122	Needle electrode, angled, 132 mm, insulated shaft 4 mm	Reusable 4 mm handles	4 mm	Needle electrode	Angled
530-122	Needle electrode, angled, 136 mm, insulated shaft 2.4 mm	Reusable 2.4 mm handles	2.4 mm	Needle electrode	Straight
520-032	Wire loop electrode, straight, Ø 10 mm, 128 mm, insulated shaft 4 mm	Reusable 4 mm handles	4 mm	Ø 10 mm wire loop electrode	Straight
530-032	Wire loop electrode, Ø 10 mm, 132 mm, insulated shaft 2.4 mm	Reusable 2.4 mm handles	2.4 mm	Ø 10 mm wire loop electrode	Straight
520-031	Wire loop electrode, straight, Ø 5 mm, 123 mm, insulated shaft 4 mm	Reusable 4 mm handles	4 mm	Ø 5 mm wire loop electrode	Straight
520-030	Ball electrode, straight, Ø 6 mm, 124 mm, insulated shaft 4 mm	Reusable 4 mm handles	4 mm	Ø 6 mm ball electrode	Straight
530-030	Ball electrode, Ø 6 mm, 128 mm, insulated shaft 2.4 mm	Reusable 2.4 mm handles	2.4 mm	Ø 6 mm ball electrode	Straight
520-035	Ball electrode, angled, Ø 6 mm, 124 mm, insulated shaft 4 mm	Reusable 4 mm handles	4 mm	Ø 6 mm ball electrode	Angled
530-035	Ball electrode, Ø 6 mm, angled, 128 mm, insulated shaft 2.4 mm	Reusable 2.4 mm handles	2.4 mm	Ø 6 mm ball electrode	Angled
520-029	Ball electrode, straight, Ø 4 mm, 122 mm, insulated shaft 4 mm	Reusable 4 mm handles	4 mm	Ø 4 mm ball electrode	Straight
530-029	Ball electrode, Ø 4 mm, 126 mm, insulated shaft 2.4 mm	Reusable 2.4 mm handles	2.4 mm	Ø 4 mm ball electrode	Straight

[Print »](#)

BOWA-electronic GmbH & Co. KG | Heinrich-Hertz-Strasse 4-10 | 72810 Gomaringen | Germany | Tel. Fon: +49 (0) 7072-6002-0