



Electrodes, short

Electric strength up to 6000Vp, hexagon coding

Heat-resistant safety insulation guarantees electric strength up to 6000Vp. Twist-proof work thanks to hexagon coding.

Intended use: Monopolar electrodes are used for electrosurgical cutting and coagulation with monopolar handles.

Packaging unit: 1 pack, each with 5 pcs.

Electric strength: 6000 Vp

Preparation: 75 cycles

Article no.	Article designation	Permissible combinations	Ø Shaft	Electrode type	Electrode shape
500-007	Knife electrode, straight, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Knife electrode	Straight
530-207	Knife electrode, straight, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Knife electrode	Straight
500-127	Knife electrode, thin, straight, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Knife electrode	Straight, fine
530-127	Knife electrode, thin, straight, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Knife electrode	Straight, fine
500-009	Knife electrode, straight, rhombic, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Knife electrode	Straight, rhombic
530-009	Knife electrode, straight, rhombic, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Knife electrode	Straight, rhombic
500-008	Knife electrode, angled, rhombic, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Knife electrode	Angled, rhombic
530-008	Knife electrode, angled, rhombic, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Knife electrode	Angled, rhombic

Article no.	Article designation	Permissible combinations	Ø Shaft	Electrode type	Electrode shape
500-126	Lancet electrode, straight, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Lancet electrode	Straight
530-126	Lancet electrode, straight, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Lancet electrode	Straight
500-125	Lancet electrode, angled, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Lancet electrode	Angled
530-125	Lancet electrode, angled, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Lancet electrode	Angled
500-011	Needle electrode, straight, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Needle electrode	Straight
530-211	Needle electrode, straight, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Needle electrode	Straight
500-124	Needle electrode, 45° angled, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Needle electrode	Angled
530-124	Needle electrode, angled, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Needle electrode	Angled
500-022	Ball electrode, straight, Ø 6 mm, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Ø 6 mm ball electrode	Straight
530-022	Ball electrode, straight, Ø 6 mm, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Ø 6 mm ball electrode	Straight
500-021	Ball electrode, straight, Ø 4 mm, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Ø 4 mm ball electrode	Straight
530-021	Ball electrode, straight, Ø 4 mm, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Ø 4 mm ball electrode	Straight
500-131	Ball electrode, angled, Ø 4 mm, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Ø 4 mm ball electrode	Angled
500-020	Ball electrode, straight, Ø 2 mm, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Ø 2 mm ball electrode	Straight
530-020	Ball electrode, straight, Ø 2 mm, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Ø 2 mm ball electrode	Straight
500-130	Ball electrode, angled, Ø 2 mm, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Ø 2 mm ball electrode	Angled
530-130	Ball electrode, Ø 2 mm, angled, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Ø 2 mm ball electrode	Angled
500-019	Ball electrode, straight, Ø 1.5 mm, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Ø 1.5 mm ball electrode	Straight

Article no.	Article designation	Permissible combinations	Ø Shaft	Electrode type	Electrode shape
500-129	Ball electrode, angled, Ø 1.5 mm, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Ø 1.5 mm ball electrode	Angled
500-016	Wire loop electrode, Ø 14 mm, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Ø 14 mm wire loop electrode	Straight
530-016	Wire loop electrode, Ø 14 mm, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Ø 14 mm wire loop electrode	Straight
500-015	Wire loop electrode, Ø 10 mm, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Ø 10 mm wire loop electrode	Straight
530-015	Wire loop electrode, Ø 10 mm, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Ø 10 mm wire loop electrode	Straight
500-014	Wire loop electrode, Ø 5 mm, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Ø 5 mm wire loop electrode	Straight
530-014	Wire loop electrode, Ø 5 mm, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Ø 5 mm wire loop electrode	Straight
500-018	Ribbon loop electrode, Ø 17 mm, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Ø 17 mm ribbon loop electrode	Straight
500-017	Ribbon loop electrode, Ø 10 mm, shaft 4 mm (5 pcs.)	Reusable 4 mm handles	4 mm	Ø 10 mm ribbon loop electrode	Straight
530-017	Ribbon loop electrode, Ø 10 mm, shaft 2.4 mm (5 pcs.)	Reusable 2.4 mm handles	2.4 mm	Ø 10 mm ribbon loop electrode	Straight

[Print »](#)

BOWA-electronic GmbH & Co. KG | Heinrich-Hertz-Strasse 4-10 | 72810 Gomaringen | Germany | Tel. Fon: +49 (0) 7072-6002-0